

## Commercial Painting Specifications Guide

### COMMERCIAL PAINTING SPECIFICATION GUIDE

#### Moorhouse Coating - Technical Standards & Requirements

#### SURFACE PREPARATION STANDARDS

- SSPC-SP1: Solvent Cleaning
- SSPC-SP2: Hand Tool Cleaning
- SSPC-SP3: Power Tool Cleaning
- SSPC-SP6: Commercial Blast Cleaning

#### COATING SYSTEMS

##### Interior Systems:

- Primer: High-adhesion latex or alkyd
- Finish: Premium acrylic or epoxy
- Coverage: 350-400 sq ft/gallon

##### Exterior Systems:

- Primer: Rust-inhibitive or masonry primer
- Finish: 100% acrylic or elastomeric
- Coverage: 250-350 sq ft/gallon

#### QUALITY STANDARDS

- Film thickness per manufacturer specs
- Surface profile requirements
- Environmental conditions for application
- Cure time requirements
- Inspection procedures

#### WARRANTY SPECIFICATIONS

- Material warranty: Per manufacturer
- Labor warranty: 2-5 years typical
- Documentation requirements
- Maintenance obligations

#### SAFETY REQUIREMENTS

- OSHA compliance mandatory
- Lead-safe practices (RRP certified)
- Proper ventilation systems
- Personal protective equipment

Contact our specification team:

[moorhousecoating.com](http://moorhousecoating.com)

(855) 666-2628